

## SINGLE CLAPPER SIAMESE CONNECTION BACK OUTLET



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 04/24/2026 07:37 AM

SKU  
: 15907

BRAND  
: DIXON VALVE

MODEL  
: ISCS4025F

Applications:

Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:

UL listed  
ULC listed  
Factory Mutual approved

Features:

The swing clapper design provides an unobstructed waterway. Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Construction:

Single swing clapper with (2) pin lug swivel inlets.

Available Options:

Other thread options are available. Consult Dixon for pricing and availability.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Branding</b>	Auto-Sprinkler
<b>Factory Part Number</b>	ISCS4025F
<b>Inlet</b>	(2) 2-1/2" female NST (NH)
<b>Material</b>	Cast Brass
<b>Maximum Operating Pressure</b>	250 PSI
<b>Origin</b>	Global
<b>Outlet</b>	4" female NPT
<b>Weight Lb</b>	7.5000