

**J-SERIES AUTOMOTIVE  
PNEUMATIC MALE THREADED  
PLUG**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/10/2026 06:12 PM

SKU

: 15948

BRAND

: DIXON VALVE

MODEL

: J4M4

Specifications:

Rated pressure for connected Steel Coupler & Steel Plug: 500 PSI (35 bar)

Maximum Working and 10,000 PSI (690 bar) Burst

Construction:

Machined components are manufactured using solid bar stock.

Compatibility & Interchange Data:

Truflate Automotive Interchange

Parker 10 Series, Rectus 55KM and Tomco A2100/PT400

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	J4M4
<b>Hex</b>	7/8"
<b>Length</b>	2.35" (59.7mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	1.01" (25.7mm)

## TECHNICAL SPECIFICATIONS

<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	NPTF
<b>Thread Size</b>	1/2"
<b>Weight Lb</b>	0.1700