

# J-SERIES AUTOMOTIVE PNEUMATIC MALE THREADED PLUG



DATE  
: 05/23/2026 07:57 AM

SKU  
: 15949

BRAND  
: DIXON VALVE

MODEL  
: J4M6

**Specifications:**

Rated pressure for connected Steel Coupler & Steel Plug: 500 PSI (35 bar)  
Maximum Working and 10,000 PSI (690 bar) Burst

**Construction:**

Machined components are manufactured using solid bar stock.

**Compatibility & Interchange Data:**

Truflate Automotive Interchange  
Parker 10 Series, Rectus 55KM and Tomco A2100/PT400

**Safety notes:**

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	J4M6
<b>Hex</b>	1-1/16"
<b>Length</b>	2.51" (63.8mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	1.23" (31.2mm)

## TECHNICAL SPECIFICATIONS

<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	NPTF
<b>Thread Size</b>	3/4"
<b>Weight Lb</b>	0.2000