

## J-SERIES AUTOMOTIVE PNEUMATIC STANDARD HOSE BARB PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/23/2026 09:00 AM

SKU  
: 24805

BRAND  
: DIXON VALVE

MODEL  
: J4S6

### Specifications:

Rated pressure for connected Steel Coupler & Steel Plug: 500 PSI (35 bar)  
Maximum Working and 10,000 PSI (690 bar) Burst

### Construction:

Machined components are manufactured using solid bar stock.

### Compatibility & Interchange Data:

Trufflate Automotive Interchange  
Parker 10 Series, Rectus 55KM and Tomco A2100/PT400

### Safety notes:

Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death. It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	J4S6
<b>Hose ID</b>	3/4"
<b>Length</b>	2.54" (64.5mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	0.94" (23.9mm)
<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Weight Lb</b>	0.1800