


DQC K-SERIES ISO-A INTERCHANGE FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/10/2026 06:46 AM

SKU

: 24821

BRAND

: DIXON VALVE

MODEL

: K16F16

Features:

Poppet style shut-off valve

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Available Options:

Contact Dixon for all available option adders

Oxy-Clean treatment is available

Compatibility & Interchange Data:

Interchangeable to ISO7241 Series 'A'

Parker 6600-Series, Aeroquip/Eaton FD56 (5600)

Faster ANV, Hansen HA 15000, Safeway S56-Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	2"
Burst Pressure	5800 PSI (400 bar)
Factory Part Number	K16F16
Hex	3"
Length	4.13" (105.0mm)
Material	Steel
Maximum OD	3.46" (87.9mm)
Maximum Operating Pressure	1450 PSI (100 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF
Thread Size	2" - 11-1/2
Weight Lb	3.6400