


DQC K-SERIES ISO-A INTERCHANGE FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/23/2026 08:44 PM

SKU
: 24847

BRAND
: DIXON VALVE

MODEL
: K6BF6-SS

Features:
Poppet style shut-off valve

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion
resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Available Options:
Contact Dixon for all available option adders
Oxy-Clean treatment is available

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'A'
Parker 6600-Series, Aeroquip/Eaton FD56 (5600)
Faster ANV, Hansen HA 15000, Safeway S56-Series

Note:
Please contact Dixon® for working pressures

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/4"
Factory Part Number	K6BF6-SS
Hex	1-5/16"
Length	2.43" (61.7mm)
Material	316 Stainless Steel
Maximum OD	1.44" (36.6mm)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP
Thread Size	3/4"-14