


DQC K-SERIES ISO-A INTERCHANGE FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/10/2026 07:31 AM

SKU
: 24851

BRAND
: DIXON VALVE

MODEL
: K8BF8

Features:
Poppet style shut-off valve

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Available Options:
Contact Dixon for all available option adders
Oxy-Clean treatment is available

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'A'
Parker 6600-Series, Aeroquip/Eaton FD56 (5600)
Faster ANV, Hansen HA 15000, Safeway S56-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 1" |
| Burst Pressure | 12400 PSI (850 bar) |
| Factory Part Number | K8BF8 |
| Hex | 1-5/8" |
| Length | 2.87" (72.9mm) |
| Material | Steel |
| Maximum OD | 1.79" (45.5mm) |
| Maximum Operating Pressure | 4000 PSI (275 bar) |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |
| Thread | Female BSPP |
| Thread Size | 1"-11 |
| Weight Lb | 0.6700 |