

**GROOVED LIGHTWEIGHT  
FLEXIBLE COUPLING- SERIES  
L, STYLE 10**

DATE  
: 07/08/2026 10:30 AM

SKU  
: 24863

BRAND  
: DIXON VALVE

MODEL  
: L03

Applications:

Applications include: general purpose, mining, irrigation, and compressed air where a deflection of 5% or less is required.

Use:

Designed for applications requiring moderate internal pressure or where weight is a factor.

Specifications:

Underwriters Listed  
Factory Mutual approved  
Bolts: 2  
Bolt Size: 1/2"  
Bolt Length: 2-3/4"

Features:

Comparable to Victaulic's #75 and Grinnell's #7000

Construction:

Rust inhibiting paint

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	L03
<b>Material</b>	Ductile Iron
<b>Maximum Operating Pressure</b>	300 PSI at 70°F (21°C)
<b>Nominal Size</b>	3"
<b>Pipe OD</b>	3.50"
<b>Seal</b>	EPDM
<b>Weight Lb</b>	2.5700