

**GROOVED LIGHTWEIGHT  
FLEXIBLE COUPLING- SERIES  
L, STYLE 10**

DATE  
: 04/22/2026 11:31 AM

SKU  
: 24867

BRAND  
: DIXON VALVE

MODEL  
: L05

Applications:

Applications include: general purpose, mining, irrigation, and compressed air where a deflection of 5% or less is required.

Use:

Designed for applications requiring moderate internal pressure or where weight is a factor.

Specifications:

Underwriters Listed

Factory Mutual approved

Bolts: 2

Bolt Size: 5/8"

Bolt Length: 3-1/4"

Features:

Comparable to Victaulic's #75 and Grinnell's #7000

Construction:

Rust inhibiting paint

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	L05
<b>Material</b>	Ductile Iron
<b>Maximum Operating Pressure</b>	300 PSI at 70°F (21°C)
<b>Nominal Size</b>	5"
<b>Pipe OD</b>	5.563"
<b>Seal</b>	EPDM
<b>Weight Lb</b>	6.2900