

**GROOVED LIGHTWEIGHT
FLEXIBLE COUPLING- SERIES
L, STYLE 10**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 11:48 AM

SKU

: 24868

BRAND

: DIXON VALVE

MODEL

: L05BU

Applications:

Applications include: general purpose, mining, irrigation, and compressed air where a deflection of 5% or less is required.

Use:

Designed for applications requiring moderate internal pressure or where weight is a factor.

Specifications:

Underwriters Listed

Factory Mutual approved

Bolts: 2

Bolt Size: 5/8"

Bolt Length: 3-1/4"

Features:

Comparable to Victaulic's #75 and Grinnell's #7000

Construction:

Rust inhibiting paint

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|------------------------|
| Factory Part Number | L05BU |
| Material | Ductile Iron |
| Maximum Operating Pressure | 300 PSI at 70°F (21°C) |
| Nominal Size | 5" |
| Pipe OD | 5.563" |
| Seal | Buna-N |
| Weight Lb | 6.3200 |