

**GROOVED LIGHTWEIGHT  
FLEXIBLE COUPLING- SERIES  
L, STYLE 10**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 11:48 AM

SKU

: 24870

BRAND

: DIXON VALVE

MODEL

: L06BU

Applications:

Applications include: general purpose, mining, irrigation, and compressed air where a deflection of 5% or less is required.

Use:

Designed for applications requiring moderate internal pressure or where weight is a factor.

Specifications:

Underwriters Listed

Factory Mutual approved

Bolts: 2

Bolt Size: 5/8"

Bolt Length: 3-1/4"

Features:

Comparable to Victaulic's #75 and Grinnell's #7000

Construction:

Rust inhibiting paint

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	L06BU
<b>Material</b>	Ductile Iron
<b>Maximum Operating Pressure</b>	300 PSI at 70°F (21°C)
<b>Nominal Size</b>	6"
<b>Pipe OD</b>	6.625"
<b>Seal</b>	Buna-N
<b>Weight Lb</b>	6.5000