

## WILKERSON FRL'S L16 ECONOMIST® COMPACT LUBRICATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 07:17 AM

SKU

: 26386

BRAND

: DIXON VALVE

MODEL

: L16-02A

### Applications:

Designed so that all of the oil flow observed in the sight dome is broken into a mist and delivered via the airflow to the application.

### Use:

The oil in the bowl can be filled or replenished without interrupting airflow or bleeding pressure from the system.

Once the oil-fill cap is removed, the bowl is depressurized and isolated from line pressure, and the bowl itself can then be removed for faster refill, if desired.

The bowl can be filled right to the top.

For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

### Features:

5 oz. bowl

Full view sight dome

Transparent Bowl

### Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Transparent Bowl
<b>Factory Part Number</b>	L16-02A
<b>Flow</b>	36.1 SCFM
<b>Maximum Operating Pressure</b>	150 PSIG (10.3 Bar)
<b>Port</b>	1/4"
<b>Temperature Range</b>	32°F to 125°F (0°C to 52°C)
<b>Weight Lb</b>	1.8400