

L17 SERIES 1 FRL'S JUMBO MICRO-FOG LUBRICATOR



DATE
: 07/08/2026 09:44 AM

SKU
: 26392

BRAND
: DIXON VALVE

MODEL
: L17-600A

Applications:

Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

Features:

- Metal Bowl with Sight Glass
- 1 qt. reservoir
- Oil level sight gauge
- One turn threaded bowl attachment permits easy maintenance

How it works:

Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir. The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

Safety notes:

- FRL's are designed for air service only, unless otherwise indicated.
- SCFM ratings at 90 PSIG inlet pressure
- Micro-fog lubricators cannot be filled under pressure.
- WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	L17-600A
Flow	160 SCFM
Inlet Pressure	250 PSI
Maximum Temperature	175°F (79°C)
Port	3/4"
Weight Lb	4.2800