

L17 SERIES 1 FRL'S JUMBO MICRO-FOG LUBRICATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 11:15 AM

SKU

: 26396

BRAND

: DIXON VALVE

MODEL

: L17-A00A

Applications:

Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

Features:

Metal Bowl with Sight Glass

1 qt. reservoir

Oil level sight gauge

One turn threaded bowl attachment permits easy maintenance

How it works:

Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.

The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

Micro-fog lubricators cannot be filled under pressure.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	L17-A00A
Flow	275 SCFM
Inlet Pressure	250 PSI
Maximum Temperature	175°F (79°C)
Port	1-1/4"
Weight Lb	3.6450