

WILKERSON FRL'S L18 ECONOMIST® COMPACT LUBRICATOR



DATE
: 07/09/2026 07:53 AM

SKU
: 26402

BRAND
: DIXON VALVE

MODEL
: L18-03AMB

Use:

To adjust and set oil delivery rate the unit must be pressurized and air must be flowing through the unit. Turn the sight dome, located on the top of the unit, counter clockwise to initiate oil delivery. If flow increases or decreases, the oil delivery rate will increase or decrease proportionally. Turning the sight dome clockwise will stop all oil delivery.

Can be filled under pressure

For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:

- Metal Bowl
- 4.09 oz. bowl
- Manual drain
- High flow capacity

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-------------------------------|
| Description | Metal Bowl |
| Factory Part Number | L18-03AMB |
| Flow | 90 SCFM |
| Maximum Operating Pressure | 250 PSIG (13.8 Bar) |
| Port | 3/8" |
| Temperature Range | 32°F to 150°F (0°C to 65.5°C) |
| Weight Lb | 2.5400 |