

**GROOVED LIGHTWEIGHT  
FLEXIBLE COUPLING- SERIES  
L, STYLE 10**

DATE  
: 07/08/2026 11:36 AM

SKU  
: 24876



BRAND  
: DIXON VALVE

MODEL  
: L215BU



Applications:  
Applications include: general purpose, mining, irrigation, and compressed air where a deflection of 5% or less is required.

Use:  
Designed for applications requiring moderate internal pressure or where weight is a factor.

Specifications:  
Underwriters Listed  
Factory Mutual approved  
Bolts: 2  
Bolt Size: 3/8"  
Bolt Length: 2-1/4"

Features:  
Comparable to Victaulic's #75 and Grinnell's #7000

Construction:  
Rust inhibiting paint

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	L215BU
<b>Material</b>	Ductile Iron
<b>Maximum Operating Pressure</b>	500 PSI at 70°F (21°C)
<b>Nominal Size</b>	1-1/2"
<b>Pipe OD</b>	1.90"
<b>Seal</b>	Buna-N
<b>Weight Lb</b>	1.5100