

**WILKERSON FRL'S L26  
ECONOMIST® STANDARD  
LUBRICATOR**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 08:18 PM

SKU

: 26407

BRAND

: DIXON VALVE

MODEL

: L26-04A

Use:

The rate of oil delivery may be controlled by turning the adjusting screw counter clockwise for more and clockwise for less oil delivery. If flow increases or decreases, the oil delivery rate will increase or decrease proportionally.

Can be filled under pressure

For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:

Transparent Bowl

10 oz. bowl

Adjustable oil feed

Quick-disconnect metal bowl guard with integral safety latch

Siphon tube filter provides clean lubricant downstream

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Transparent Bowl
<b>Factory Part Number</b>	L26-04A
<b>Flow</b>	128 SCFM
<b>Maximum Operating Pressure</b>	150 PSIG (10.3 Bar)
<b>Port</b>	1/2"
<b>Temperature Range</b>	32°F to 125°F (0°C to 52°C)
<b>Weight Lb</b>	2.2700