

WILKERSON FRL'S L28 ECONOMIST® STANDARD LUBRICATOR



DATE
: 04/23/2026 10:12 PM

SKU
: 26410

BRAND
: DIXON VALVE

MODEL
: L28-03AMB

Use:

To adjust and set oil delivery rate the unit must be pressurized and air must be flowing through the unit. Turn the sight dome, located on the top of the unit, counter clockwise to initiate oil delivery. If flow increases or decreases, the oil delivery rate will increase or decrease proportionally. Turning the sight dome clockwise will stop oil delivery.

Can be filled under pressure

For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:

- 6.11 oz. bowl
- Metal Bowl
- Manual drain
- High flow capacity

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Description	Metal Bowl
Factory Part Number	L28-03AMB
Flow	110 SCFM
Maximum Operating Pressure	250 PSIG (17.2 Bar)
Port	3/8"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	2.4300