

## VENT-LOCK? SAFETY CAM & GROOVE TYPE A ADAPTER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 09:05 AM

SKU

: 16233

BRAND

: DIXON VALVE

MODEL

: L400-A-AL

Applications:

Transfer of fluids and solids, with a safer disconnection

Use:

Can be used with ferrules, sleeves, bands and other reliable attachment options

Features:

Safety release cam and groove couplings permit the release of static pressure when disconnecting hose assemblies

Venting system protects operator from being sprayed with hazardous or non-hazardous fluids or solids

US Pat. 934759, CDN Pat. 277866

Available Options:

Consult Dixon for availability of other materials

Safety notes:

Pressure rating recommendation is based on the use of mating Vent-Lock™ L-style fittings at ambient temperature 70°F (21°C) with standard Buna-N seal installed, for use at elevated temperature or other unusual operating conditions, consult Dixon.

Does not interchange with standard cam and groove products use only with Vent-Lock™ L-style fittings.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Material</b>	Aluminum
<b>Factory Part Number</b>	L400-A-AL
<b>Size</b>	4"
<b>Weight Lb</b>	1.8500
<b>Working Pressure</b>	150 PSI with King Crimp ferrules, crimp sleeves and bands at 100 PSI