

WILKERSON FRL'S L40 & L50 ECONOMIST® STANDARD LUBRICATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 10:13 PM

SKU

: 26422

BRAND

: DIXON VALVE

MODEL

: L50-0CAMB

Use:

The rate of oil delivery may be controlled by turning the adjusting screw counter clockwise for more and clockwise for less oil delivery. The oil delivery rate will change automatically to deliver more oil during higher air flows and less oil for air flows lower than the one at which the setting was made.

Can be filled under pressure

For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:

26 oz. bowl

Metal Bowl

Manual drain with sight glass

Full view sight dome

Adjustable oil feed

Quick-disconnect clamp ring for easy bowl removal

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 120 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|---|
| Description | Metal Bowl, manual drain with sight glass |
| Factory Part Number | L50-0CAMB |
| Flow | 1186 SCFM |
| Maximum Operating Pressure | 200 PSIG (13.8 Bar) |
| Port | 2" |
| Temperature Range | 32°F to 150°F (0°C to 65.5°C) |
| Weight Lb | 10.5600 |