

## L73 SERIES 1 FRL'S COMPACT MICRO-FOG LUBRICATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 04/21/2026 09:34 PM

SKU  
: 26435

BRAND  
: DIXON VALVE

MODEL  
: L73M-2MB

### Applications:

Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

### Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

### Features:

- Metal Bowl
- 4 oz. reservoir
- Quick release bayonet bowl
- Micro-fog design delivers aerosol mist

### How it works:

Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.

The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

### Installation

In-line or modular installation

### Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

Micro-fog lubricators cannot be filled under pressure.

Pressure rating given at ambient temperature 70°F/21°C.

SCFM ratings at 90 PSIG inlet pressure

## TECHNICAL SPECIFICATIONS

|                                   |              |
|-----------------------------------|--------------|
| <b>Description</b>                | Metal Bowl   |
| <b>Factory Part Number</b>        | L73M-2MB     |
| <b>Flow</b>                       | 70 SCFM      |
| <b>Maximum Operating Pressure</b> | 250 PSI      |
| <b>Maximum Temperature</b>        | 175°F (79°C) |
| <b>Port</b>                       | 1/4"         |
| <b>Weight Lb</b>                  | 1.2700       |