

## SERIES 1 FRL'S COMPACT MICRO-FOG LUBRICATOR WITH HIGH PRESSURE SIGHT FEED DOME



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 02:26 PM

SKU

: 26438

BRAND

: DIXON VALVE

MODEL

: L73M-3MBPX

### Applications:

Designed for use with alcohol or other anti-freeze agents when units are installed in cold temperature environments.

Micro-fog lubricators are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

### Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F (38°C)

### Features:

Metal Bowl with Sight Glass

4 oz. reservoir

Quick release bayonet bowl

Micro-fog design delivers aerosol mist

### Construction:

High pressure sight feed dome with aluminum case and fluorocarbon O-rings and seals

High pressure sight glass on bowls and metal petcock drain

### How it works:

Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.

The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

### Installation

In-line or modular installation

Safety notes:  
FRL's are designed for air service only, unless otherwise indicated.  
Micro-fog lubricators cannot be filled under pressure.  
Pressure rating given at ambient temperature 70°F/21°C.  
SCFM ratings at 90 PSIG inlet pressure  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	L73M-3MBPX
<b>Flow</b>	60 SCFM
<b>Maximum Temperature</b>	175°F (79°C)
<b>Port</b>	3/8"
<b>Weight Lb</b>	0.9500