

## L74 SERIES 1 FRL'S STANDARD OIL-FOG LUBRICATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 11:27 AM

SKU

: 26442

BRAND

: DIXON VALVE

MODEL

: L74C-3

Applications:

Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.

Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

Features:

Transparent Bowl

7 oz. reservoir

Quick release bayonet bowl

Can be filled under pressure

How it works:

All the oil visible dropping through the transparent sight-feed dome goes to the airstream.

Installation

In-line or modular installation

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

Pressure rating given at ambient temperature 70°F.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Transparent Bowl
<b>Factory Part Number</b>	L74C-3
<b>Flow</b>	118 SCFM
<b>Maximum Operating Pressure</b>	150 PSI
<b>Maximum Temperature</b>	125°F (52°C)
<b>Port</b>	3/8"
<b>Weight Lb</b>	1.8400