

L74 SERIES 1 FRL'S STANDARD OIL-FOG LUBRICATOR



DATE
: 07/08/2026 12:18 PM

SKU
: 26443

BRAND
: DIXON VALVE

MODEL
: L74C-3MB

Applications:

Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.

Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

Features:

- Metal Bowl
- 7 oz. reservoir
- Quick release bayonet bowl
- Can be filled under pressure

How it works:

All the oil visible dropping through the transparent sight-feed dome goes to the airstream.

Installation

In-line or modular installation

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

Pressure rating given at ambient temperature 70°F.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Description	Metal Bowl
Factory Part Number	L74C-3MB
Flow	118 SCFM
Maximum Operating Pressure	250 PSI
Maximum Temperature	175°F (79°C)
Port	3/8"
Weight Lb	1.8200