

L74 SERIES 1 FRL'S STANDARD OIL-FOG LUBRICATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 04/21/2026 09:38 PM

SKU
: 26444

BRAND
: DIXON VALVE

MODEL
: L74C-4

Applications:

Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.

Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

Features:

- Transparent Bowl
- 7 oz. reservoir
- Quick release bayonet bowl
- Can be filled under pressure

How it works:

All the oil visible dropping through the transparent sight-feed dome goes to the airstream.

Installation

In-line or modular installation

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

Pressure rating given at ambient temperature 70°F.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Transparent Bowl
Factory Part Number	L74C-4
Flow	192 SCFM
Maximum Operating Pressure	150 PSI
Maximum Temperature	125°F (52°C)
Port	1/2"
Weight Lb	1.7500