

L74 SERIES 1 FRL'S STANDARD OIL-FOG LUBRICATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 11:17 AM

SKU

: 26447

BRAND

: DIXON VALVE

MODEL

: L74C-6MB

Applications:

Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.

Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

Features:

Metal Bowl

7 oz. reservoir

Quick release bayonet bowl

Can be filled under pressure

How it works:

All the oil visible dropping through the transparent sight-feed dome goes to the airstream.

Installation

In-line or modular installation

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

Pressure rating given at ambient temperature 70°F.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|--------------|
| Description | Metal Bowl |
| Factory Part Number | L74C-6MB |
| Flow | 186 SCFM |
| Maximum Operating Pressure | 250 PSI |
| Maximum Temperature | 175°F (79°C) |
| Port | 3/4" |
| Weight Lb | 1.7500 |