

## L74 SERIES 1 FRL'S STANDARD OIL-FOG LUBRICATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 04/21/2026 11:18 PM

SKU  
: 26447

BRAND  
: DIXON VALVE

MODEL  
: L74C-6MB

### Applications:

Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.

### Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

### Features:

- Metal Bowl
- 7 oz. reservoir
- Quick release bayonet bowl
- Can be filled under pressure

### How it works:

All the oil visible dropping through the transparent sight-feed dome goes to the airstream.

### Installation

In-line or modular installation

### Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

Pressure rating given at ambient temperature 70°F.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Description</b>	Metal Bowl
<b>Factory Part Number</b>	L74C-6MB
<b>Flow</b>	186 SCFM
<b>Maximum Operating Pressure</b>	250 PSI
<b>Maximum Temperature</b>	175°F (79°C)
<b>Port</b>	3/4"
<b>Weight Lb</b>	1.7500