

## L74 SERIES 1 FRL'S STANDARD MICRO-FOG LUBRICATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 10:25 AM

SKU

: 26451

BRAND

: DIXON VALVE

MODEL

: L74M-4MB

Applications:

Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

Features:

Metal Bowl

7 oz. reservoir

Quick release bayonet bowl

Micro-fog design delivers aerosol mist

How it works:

Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.

The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

Installation

In-line or modular installation

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

Micro-fog lubricators cannot be filled under pressure.

Pressure rating given at ambient temperature 70°F.

SCFM ratings at 90 PSIG inlet pressure

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Metal Bowl
<b>Factory Part Number</b>	L74M-4MB
<b>Flow</b>	154 SCFM
<b>Maximum Operating Pressure</b>	250 PSI
<b>Maximum Temperature</b>	175°F (79°C)
<b>Port</b>	1/2"
<b>Weight Lb</b>	1.7800