

## L74 SERIES 1 FRL'S STANDARD MICRO-FOG LUBRICATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 04/21/2026 09:36 PM

SKU  
: 26452

BRAND  
: DIXON VALVE

MODEL  
: L74M-6

### Applications:

Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

### Use:

Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

### Features:

- Transparent Bowl
- 7 oz. reservoir
- Quick release bayonet bowl
- Micro-fog design delivers aerosol mist

### How it works:

Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.

The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

### Installation

In-line or modular installation

### Safety notes:

- FRL's are designed for air service only, unless otherwise indicated.
- Micro-fog lubricators cannot be filled under pressure.
- Pressure rating given at ambient temperature 70°F.
- SCFM ratings at 90 PSIG inlet pressure

## TECHNICAL SPECIFICATIONS

<b>Description</b>	Transparent Bowl
<b>Factory Part Number</b>	L74M-6
<b>Flow</b>	142 SCFM
<b>Maximum Operating Pressure</b>	150 PSI
<b>Maximum Temperature</b>	125°F (52°C)
<b>Port</b>	3/4"
<b>Weight Lb</b>	1.7100