

## WILKERSON FRL'S M16 COMPACT MODULAR COALESCING FILTER



DATE  
: 07/09/2026 08:54 AM

SKU  
: 26457

BRAND  
: DIXON VALVE

MODEL  
: M16-03M

**Applications:**

For removal of extremely fine oil mists, oil aerosols and microscopic particles

**Use:**

A standard airline filter should be installed as a pre-filter when using a coalescing filter.

**Features:**

Manual Drain

Transparent Bowl and Guard

0.01 micron type C element

5 oz. bowl

The differential pressure indicator changes from green to red with pressure loss

**Available Options:**

0.5 micron type B and 0.003 micron type D elements are optional

**Installation**

Can be installed in modular system

**Safety notes:**

FRL's are designed for air service only, unless otherwise indicated.

A standard airline filter should be installed as a pre-filter when using a coalescing filter.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Description</b>	Manual Drain
<b>Factory Part Number</b>	M16-03M
<b>Flow</b>	44.7 SCFM
<b>Maximum Operating Pressure</b>	150 PSIG (10.3 Bar)
<b>Port</b>	3/8"
<b>Temperature Range</b>	32°F to 125°F (0°C to 52°C)
<b>Weight Lb</b>	2.0180