

## WILKERSON FRL'S M18 COMPACT MODULAR COALESCING FILTER



DATE  
: 07/09/2026 08:56 AM

SKU  
: 26460

BRAND  
: DIXON VALVE

MODEL  
: M18-02A

### Applications:

High-efficiency removal of water, oil aerosols, and solid particulate contaminants down to 0.01 mg/m<sup>3</sup> with minimum pressure drop

### Use:

A standard airline filter should be installed as a pre-filter when using a coalescing filter.

### Features:

Modern design and appearance

Light weight

High flow capacity

4 oz. bowl

The differential pressure indicator changes from green to red with pressure loss

### Construction:

Transparent bowl and guard

### Available Options:

0.5 micron type B and 0.003 micron type D elements are optional

### Installation

Can be installed in modular system

### Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

A standard airline filter should be installed as a pre-filter when using a coalescing filter.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

|                                   |                             |
|-----------------------------------|-----------------------------|
| <b>Description</b>                | Automatic Drain             |
| <b>Factory Part Number</b>        | M18-02A                     |
| <b>Flow</b>                       | 36 SCFM                     |
| <b>Maximum Operating Pressure</b> | 150 PSIG (10.3 Bar)         |
| <b>Size</b>                       | 1/4"                        |
| <b>Temperature Range</b>          | 32°F to 125°F (0°C to 52°C) |
| <b>Weight Lb</b>                  | 1.1000                      |