

## WILKERSON FRL'S M18 COMPACT MODULAR COALESCING FILTER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 11:56 PM

SKU

: 26462

BRAND

: DIXON VALVE

MODEL

: M18-03A

Applications:

High-efficiency removal of water, oil aerosols, and solid particulate contaminants down to 0.01 mg/m<sup>3</sup> with minimum pressure drop

Use:

A standard airline filter should be installed as a pre-filter when using a coalescing filter.

Features:

Modern design and appearance

Light weight

High flow capacity

4 oz. bowl

The differential pressure indicator changes from green to red with pressure loss

Construction:

Transparent bowl and guard

Available Options:

0.5 micron type B and 0.003 micron type D elements are optional

Installation

Can be installed in modular system

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

A standard airline filter should be installed as a pre-filter when using a coalescing filter.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Automatic Drain
<b>Factory Part Number</b>	M18-03A
<b>Flow</b>	36 SCFM
<b>Maximum Operating Pressure</b>	150 PSIG (10.3 Bar)
<b>Size</b>	3/8"
<b>Temperature Range</b>	32°F to 125°F (0°C to 52°C)
<b>Weight Lb</b>	1.1000