

## WILKERSON FRL'S M26 STANDARD MODULAR COALESCING FILTER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability



DATE  
: 07/09/2026 08:57 AM

SKU  
: 26466

BRAND  
: DIXON VALVE

MODEL  
: M26-03A

#### Applications:

For the removal of extremely fine oil mists, oil aerosols and microscopic particles

#### Use:

Can be installed in modular system

#### Features:

Automatic Drain  
Transparent Bowl and Guard  
0.01 micron type C element  
10 oz. bowl

Differential pressure indicator changes from green to red with pressure loss

#### Available Options:

0.5 micron type B and 0.003 micron type D elements are optional

#### Safety notes:

FRL's are designed for air service only, unless otherwise indicated.  
A standard airline filter should be installed as a pre-filter when using a coalescing filter.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Description</b>	Automatic Drain, Transparent Bowl and Guard
<b>Factory Part Number</b>	M26-03A
<b>Flow</b>	65.5 SCFM
<b>Maximum Operating Pressure</b>	150 PSIG (10.3 Bar)
<b>Port</b>	3/8"
<b>Temperature Range</b>	32°F to 125°F (0°C to 52°C)
<b>Weight Lb</b>	2.5850