

**WILKERSON FRL'S M26
STANDARD MODULAR
COALESCING FILTER**



DATE
: 04/23/2026 11:57 PM

SKU
: 26466

BRAND
: DIXON VALVE

MODEL
: M26-03A

Applications:
For the removal of extremely fine oil mists, oil aerosols and microscopic particles

Use:
Can be installed in modular system

Features:
Automatic Drain
Transparent Bowl and Guard
0.01 micron type C element
10 oz. bowl
Differential pressure indicator changes from green to red with pressure loss

Available Options:
0.5 micron type B and 0.003 micron type D elements are optional

Safety notes:
FRL's are designed for air service only, unless otherwise indicated.
A standard airline filter should be installed as a pre-filter when using a coalescing filter.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Description	Automatic Drain, Transparent Bowl and Guard
Factory Part Number	M26-03A
Flow	65.5 SCFM
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	2.5850