

WILKERSON FRL'S M26 STANDARD MODULAR COALESCING FILTER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 11:56 PM

SKU

: 26468

BRAND

: DIXON VALVE

MODEL

: M26-04M

Applications:

For the removal of extremely fine oil mists, oil aerosols and microscopic particles

Use:

Can be installed in modular system

Features:

Manual Drain

Transparent Bowl and Guard

0.01 micron type C element

10 oz. bowl

Differential pressure indicator changes from green to red with pressure loss

Available Options:

0.5 micron type B and 0.003 micron type D elements are optional

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

A standard airline filter should be installed as a pre-filter when using a coalescing filter.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	M26-04M
Flow	79.5 SCFM
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	1/2"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	2.5200