

WILKERSON FRL'S M28 STANDARD MODULAR COALESCING FILTER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 11:59 PM

SKU

: 26469

BRAND

: DIXON VALVE

MODEL

: M28-03A

Applications:

High-efficiency removal of water, oil aerosols, and solid particulate contaminants down to 0.01 mg/m³ with minimum pressure drop

Use:

Can be installed in modular system

Features:

Modern design and appearance

Light weight

High flow capacity

6 oz. bowl

Differential pressure indicator changes from green to red with pressure loss

Construction:

Transparent bowl and guard

Available Options:

0.5 micron type B and 0.003 micron type D elements are optional

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

A standard airline filter should be installed as a pre-filter when using a coalescing filter.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Automatic Drain
Factory Part Number	M28-03A
Flow	42 SCFM
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Size	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	1.7600