

WILKERSON FRL'S M28 STANDARD MODULAR COALESCING FILTER



DATE
: 07/09/2026 10:00 AM

SKU
: 26474

BRAND
: DIXON VALVE

MODEL
: M28-06M

Applications:
High-efficiency removal of water, oil aerosols, and solid particulate contaminants down to 0.01 mg/m³ with minimum pressure drop

Features:
Modern design and appearance
Light weight
High flow capacity
6 oz. bowl
Differential pressure indicator changes from green to red with pressure loss

Construction:
Transparent bowl and guard

Available Options:
0.5 micron type B and 0.003 micron type D elements are optional

Safety notes:
FRL's are designed for air service only, unless otherwise indicated.
A standard airline filter should be installed as a pre-filter when using a coalescing filter.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Description	Manual Drain
Factory Part Number	M28-06M
Flow	40 SCFM
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Size	3/4"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	1.7600