

## M-SERIES ARO PNEUMATIC FEMALE THREADED PLUG



DATE  
: 07/11/2026 08:37 AM

SKU  
: 24937

BRAND  
: DIXON VALVE

MODEL  
: M2F3

### Specifications:

Rated pressure for connected Auto Steel Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 2,600 PSI (179 bar) Burst

Rated pressure for connected Manual Steel Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 12,400 PSI (855 bar) Burst

### Construction:

Machined components are manufactured using solid bar stock.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

### Compatibility & Interchange Data:


Automatic couplings interchange with ARO 210/310 and Hansen 210/310

Manual Couplings Interchange with Parker 50-Series and Amflow Type 'B'

### Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/4"
<b>Factory Part Number</b>	M2F3
<b>Hex</b>	7/8"
<b>Length</b>	1.57"
<b>Material</b>	Steel
<b>Maximum OD</b>	1.01"
<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	NPTF
<b>Thread Size</b>	3/8"
<b>Weight Lb</b>	0.1000