

M-SERIES ARO PNEUMATIC STANDARD HOSE BARB PLUG



DATE
: 05/23/2026 10:23 PM

SKU
: 24943

BRAND
: DIXON VALVE

MODEL
: M2S3

Specifications:

Rated pressure for connected Auto Steel Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 2,600 PSI (179 bar) Burst

Rated pressure for connected Manual Steel Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 12,400 PSI (855 bar) Burst

Construction:

Machined components are manufactured using solid bar stock.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

Automatic couplings interchange with ARO 210/310 and Hansen 210/310

Manual Couplings Interchange with Parker 50-Series and Amflo Type 'B'

Safety notes:

Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application.

Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death.

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	M2S3
Hose ID	3/8"
Length	2.00"
Material	Steel
Maximum OD	0.56"
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Weight Lb	0.0500