

**DIX-LOCK® N-SERIES
INTERCHANGE MALE HEAD X
MALE THREADED
SAFETY-LOCK END PLUG**



DATE
: 04/29/2026 05:05 AM

SKU
: 25102

BRAND
: DIXON VALVE

MODEL
: N4M6-ZLS



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

Specifications:
Rated pressure for connected Steel Coupler & Steel Plug: 500 PSI (35 bar)
Maximum Working and 11,000 PSI (755 bar) Burst
Conforms to MIL-C-3486 and A-A-50431A standards

Construction:
Machined components are manufactured using solid bar stock.
Stainless steel retaining ring and spring maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Coupling sleeve constructed of cast zinc steel
Steel lock ring

Available Options:
316 stainless steel available in some versions upon request, contact Dixon

Compatibility & Interchange Data:
Bows Interchange Bayonet Style
Interchangeable with Bowses 51000-Series, National Series 'B', MacDonald Quick-Action, Campbell Single-Lock

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Hex	1-3/16"
Length	3.65" (92.7mm)
Material	Steel
Maximum OD	1.31" (33.3mm)
Factory Part Number	N4M6-ZLS
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPTF
Thread Size	3/4"
Weight Lb	0.7000