

## DIX-LOCK® N-SERIES INTERCHANGE MALE END X HOSE BARB PLUG



DATE  
: 07/10/2026 09:13 AM

SKU  
: 25117

BRAND  
: DIXON VALVE

MODEL  
: N4S6-B

### Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 Bar)  
Maximum Working and 8,200 PSI (865 Bar) Burst  
Conforms to MIL-C-3486 and A-A-50431A standards

### Construction:

Machined components are manufactured using solid bar stock.  
Stainless steel retaining ring and spring maximize corrosion resistance and extend service life.  
Coupling sleeve constructed of cast zinc steel

### Available Options:

Staked ferrule option available, contact Dixon  
316 stainless steel available in some versions upon request, contact Dixon

### Compatibility & Interchange Data:

Bowes Interchange Bayonet Style  
Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald Quick-Action, Campbell Single-Lock

### Safety notes:

Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death. It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	N4S6-B
<b>Hose ID</b>	3/4"
<b>Length</b>	4.95" (125.7mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	1.40" (35.6mm)
<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Weight Lb</b>	0.7700