

**FACTORY SET PRESSURE
REDUCING BRASS GLOBE
VALVE GROOVED X GROOVED**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 04:31 PM

SKU

: 17004

BRAND

: DIXON VALVE

MODEL

: NAPRVGT250-55

Use:

2-1/2" size reduces inlet pressures of 400 PSI (2758 kPa) or less to desired working pressures from 20 through 175 PSI (138-1207 kPa) under discharge or static conditions.

Specifications:

UL listed for Automatic Sprinkler Systems as floor or zone control valve

Standpipe Systems, Class I, II and III

Automatic Check Valve for Dual Riser Systems

Approved by the New York City Board of Standards and Appeals, approval #

MEA 54-07-E

Approved by the City of Los Angeles and the City of San Francisco (ULC

2-1/2")

Features:

Tamper resistant

True combination shut-off and pressure reducing valve

Construction:

Cast brass

(4) drilled and tapped bosses: two on each side for upstream and downstream pressure monitoring. Saves installation time and provides a cleaner appearance.

Available Options:

Valves are available with a tamper proof switch as an accessory device to hasten valve operation while monitoring its open condition. The complete switch, with bracket and housing, is available for field mounting. Consult Dixon for price and availability.

Safety notes:

TECHNICAL SPECIFICATIONS

Description	Calculated setting: 55
Inlet	2-1/2" grooved
Material	Cast Brass
Maximum Operating Pressure	400 PSI
Outlet	2-1/2" grooved
Factory Part Number	NAPRVGT250-55
Weight Lb	27.0200