

**NK-SERIES JAPANESE  
PNEUMATIC FEMALE  
THREADED PLUG**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/11/2026 01:18 PM

SKU  
: 17049

BRAND  
: DIXON VALVE

MODEL  
: NK2BF2

Construction:  
Machined components are manufactured using solid steel bar stock.  
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:  
Japanese Industrial Interchange Pneumatic Coupling  
Nitto Kohki Hi-cupla 200, Rectus Series 13 and CEJN Series 315

Safety notes:  
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	1/4"
<b>Burst Pressure</b>	13500 PSI
<b>Factory Part Number</b>	NK2BF2
<b>Hex</b>	5/8"
<b>Length</b>	1.39"
<b>Material</b>	Steel
<b>Maximum OD</b>	0.52"
<b>Maximum Operating Pressure</b>	300 PSI

## TECHNICAL SPECIFICATIONS

<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	BSPP
<b>Thread Size</b>	1/4"
<b>Weight Lb</b>	0.0500