

NK-SERIES JAPANESE PNEUMATIC MALE THREADED PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/24/2026 04:12 AM

SKU

: 17052

BRAND

: DIXON VALVE

MODEL

: NK2M2

Construction:

Machined components are manufactured using solid steel bar stock.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

Japanese Industrial Interchange Pneumatic Coupling

Nitto Kohki Hi-cupla 200, Rectus Series 13 and CEJN Series 315

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	13500 PSI
Factory Part Number	NK2M2
Hex	5/8"
Length	1.54"
Material	Steel
Maximum OD	0.52"
Maximum Operating Pressure	300 PSI

TECHNICAL SPECIFICATIONS

Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	1/4"
Weight Lb	0.0600