

## DUAL-LOCK P-SERIES THOR INTERCHANGE MALE THREAD PLUG



DATE  
: 07/10/2026 12:29 PM

SKU  
: 17165

BRAND  
: DIXON VALVE

MODEL  
: P4M6-B

Construction:  
Machined components are manufactured using solid bar stock.  
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:  
Thor Finger-Lock Interchange  
Interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings

Safety notes:  
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/2"
<b>Burst Pressure</b>	3500 PSI (240 bar)
<b>Factory Part Number</b>	P4M6-B
<b>Length</b>	2.55" (64.8mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	1.55" (39.4mm)
<b>Maximum Operating Pressure</b>	300 PSI (20 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)

\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Thread</b>	NPTF
<b>Thread Size</b>	3/4"
<b>Weight Lb</b>	0.4800
<b>Wrench Flat</b>	1-1/8"