

DUAL-LOCK P-SERIES THOR INTERCHANGE MALE THREAD PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/23/2026 02:04 AM

SKU
: 17166

BRAND
: DIXON VALVE

MODEL
: P4M6-S

Construction:
Machined components are manufactured using solid bar stock.
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:
Thor Finger-Lock Interchange
Interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 1/2" |
| Burst Pressure | 4500 PSI (310 bar) |
| Factory Part Number | P4M6-S |
| Length | 2.55" (64.8mm) |
| Material | 303 Stainless Steel |
| Maximum OD | 1.55" (39.4mm) |
| Maximum Operating Pressure | 300 PSI (20 bar) |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |

TECHNICAL SPECIFICATIONS

| | |
|--------------------|--------|
| Thread | NPTF |
| Thread Size | 3/4" |
| Weight Lb | 0.4600 |
| Wrench Flat | 1-1/8" |