

DUAL-LOCK P-SERIES THOR INTERCHANGE MALE THREAD PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/23/2026 02:04 AM

SKU

: 17168

BRAND

: DIXON VALVE

MODEL

: P4M8-B

Construction:

Machined components are manufactured using solid bar stock.

Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:

Thor Finger-Lock Interchange

Interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	3500 PSI (240 bar)
Factory Part Number	P4M8-B
Length	3.25" (82.6mm)
Material	Brass
Maximum OD	1.55" (39.4mm)
Maximum Operating Pressure	300 PSI (20 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)

TECHNICAL SPECIFICATIONS

Thread	NPTF
Thread Size	1"
Weight Lb	0.8700
Wrench Flat	1-3/8"