

## STAINLESS PANEL BUILDER GAUGE



DATE  
: 07/08/2026 11:12 AM

SKU  
: 17177

BRAND  
: DIXON VALVE

MODEL  
: PBLSS200

### Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

### Use:

Suitable for corrosive environments  
Used in gaseous and liquid media

### Specifications:

ASME B40.100 Grade A  $\pm$  2-1-2% full scale accuracy

### Features:

Fits industry standard 2.56" panel hole cutout

### Construction:

316L stainless steel wetted parts materials  
304 stainless steel case and ring  
Dial- white aluminum with black lettering; stop pin  
Pointer- black aluminum  
Glycerin filled  
Laminated safety glass window lens

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	PBLSS200
<b>Figure Interval</b>	50
<b>Material</b>	Stainless Steel
<b>Minor Gradient</b>	5
<b>Mount</b>	1/4" Lower Back Mount
<b>Pressure Range</b>	0-200 PSI
<b>Size</b>	2-1/2" Face
<b>Temperature Range</b>	-4°F to 140°F (-20°C to 60°C)
<b>Temperature Rating</b>	212°F (100°C) maximum media temperature
<b>Weight Lb</b>	0.4900