

STAINLESS PANEL BUILDER GAUGE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 11:11 AM

SKU
: 17183

BRAND
: DIXON VALVE

MODEL
: PBLSS5000

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Use:

Suitable for corrosive environments
Used in gaseous and liquid media

Specifications:

ASME B40.100 Grade A \pm 2-1-2% full scale accuracy

Features:

Fits industry standard 2.56" panel hole cutout

Construction:

316L stainless steel wetted parts materials
304 stainless steel case and ring
Dial- white aluminum with black lettering; stop pin
Pointer- black aluminum
Glycerin filled
Laminated safety glass window lens

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	PBLSS5000
Figure Interval	1000
Material	Stainless Steel
Minor Gradient	100
Mount	1/4" Lower Back Mount
Pressure Range	0-5000 PSI
Size	2-1/2" Face
Temperature Range	-4°F to 140°F (-20°C to 60°C)
Temperature Rating	212°F (100°C) maximum media temperature
Weight Lb	0.6500