

PD-SERIES DIAGNOSTIC MALE PLUG



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 06/15/2026 11:04 PM

SKU
: 17204

BRAND
: DIXON VALVE

MODEL
: PD10M2

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Compatibility & Interchange Data:
Interchangeable to ISO15171-1
Parker PD-Series, Aeroquip FD90

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/8"
Burst Pressure	18700 PSI (1300 bar)
Factory Part Number	PD10M2
Hex	17mm
Length	1.93" (49.0mm)
Material	Steel
Maximum OD	0.76" (19.3mm)
Maximum Operating Pressure	6000 PSI (400 bar) at 70°F (21°C)
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Thread	Male ORB

TECHNICAL SPECIFICATIONS

Thread Size	7/16"-20
Weight Lb	0.1100